



CIE-8088A

MULTÍMETRO DIGITAL AUTOMOTRIZ

- * 6600 counts, bar-graph, Dual display
- * Auto ranging
- * Auto power off
- * Overload protections
- * Safety input jacks
- * Safety test leads
- * Safety: EN61010-1, CAT IV 600V, CAT III 1000V, CE approved
- * Dimensions: 198mm(H)×90mm(W)×44mm(D)
- * Weight: Approx. 400g

SPECIFICATIONS

- * RPM: 600 ~ 6600 (RPM), 6600 ~ 12000 (x10RPM) ±2.0%
- * Dwell angle: 4, 5, 6, 8 cylinders ±2.0%
- * ms pulse width: 0.1ms to 10ms ±2.0%
- * Duty cycle: 5% ~ 95% >100µs, <100ms ±2.0%
- * DC Volts: 660mV, 6.6V, 66V, 660V, 1000V ±0.5%
- * AC Volts: 660mV, 6.6V, 66V, 660V, 750V ±1.5% (50~500Hz)
- * DC Current: 660µA, 6600µA, 66mA, 400mA, 20A ±1.0%
- * AC Current: 660µA, 6600µA, 66mA, 400mA, 20A ±1.5%(50~500Hz)
- * Resistance: 660Ω, 6.6kΩ, 66kΩ, 660kΩ, 6.6MΩ, 66MΩ ±1.0%
- * Capacitance: 6.6nF, 66nF, 660nF, 6.6µF, 66µF, 660µF, 6.6mF ±3.0%
- * Temperature: -20°C ~ 1000°C, -4°F ~ 1832°F ±1.0%,
K-type thermocouple
- * Frequency: 10Hz~200kHz ±0.1%
- * Diode Test
- * Continuity Test
- * DATA Hold
- * MAX / MIN Hold
- * Δ(Relative)
- * Backlight
- * Resolution: 1RPM, 0.1mV, 0.1µA, 0.1Ω, 1pF, 0.01Hz, 0.1°C, 0.1°F