6-219590-4 | TE510M-GYMI-AP



510 Series Copper Cable, category 5e, 4 pair, U/UTP, 24 AWG, 305m, gray

OBSOLETE

This product was discontinued on: March 22, 2019

Replaced By:

884024914/10 ETL Verified Category 5e U/UTP Cable, non-plenum, gray jacket, 4 pair count, 1000 CS24CM GRY C5E 4/24 U/UTP CPK 305M ft (305 m) length, CommPak

Product Classification

Regional Availability Asia

Portfolio NETCONNECT®

Product Type Twisted pair cable

Product Series 510 Series

General Specifications

Product Number 510M **ANSI/TIA Category** 5e

Cable Component Type Horizontal

Cable Type U/UTP (unshielded)

Conductor Type, singlesSolidConductors, quantity8Jacket ColorGrayPairs, quantity4

Transmission Standards ANSI/TIA-568.2-D | CENELEC EN 50288-6-1 | ISO/IEC 11801 Class D

Dimensions

Cable Length 304.8 m | 1000 ft



6-219590-4 | TE510M-GYMI-AP


Diameter Over Jacket, nominal

4.902 mm | 0.193 in

Conductor Gauge, singles

24 AWG

Cross Section Drawing



Electrical Specifications

Operating Voltage, maximum 80 V

Remote Powering Fully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery

of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1,

CENELEC EN 50174-2 or TIA TSB-184-A

Material Specifications

Conductor MaterialBare copperInsulation MaterialPolyolefin

Jacket Material PVC

Environmental Specifications

Operating Temperature -20 °C to +60 °C (-4 °F to +140 °F)

Packaging and Weights

Packaging Type Reelex



6-219590-4 | TE510M-GYMI-AP

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

